LESSMANN®
THE GERMAN BRUSH COMPANY

DATASHEET

Sealing brush with straight fittings

ArtNr. 22135310

Sealing brushes type FH22 backing width 6 mm holder height 22 mm horsehair mixed ROS/PE (70%/30%) grey natural/0.15 mm brush backing iron sheet galvanized



Characteristics

Technical data

Art. Description ERP	Sealing brushes type FH22 backing width 6 mm holder height 22 mm horsehair mixed ROS/PE (70%/30%) grey natural/0.15 mm brush backing iron sheet galvanized
Brush Overall Length [GL]	variabel mm
Overall Height [GH]	variabel mm
Filling Height [H]	variabel mm
Filling Material Diameter	natur/0.15 mm
Net weight	0.395 kg
Leg Height [FH]	22 mm
Backing Width [RB]	6 mm
Brush Length [L]	variabel mm
Filling Height Visible [HS]	variabel mm
Backing Height [SH]	7.0 mm
Filling material	ROS/PE (70%/30%)
Filling Material Shape	-
Brush Shape	Strip-shaped
Strip Brush Type	Type FH22
Slit Strip Material	Galvanised
Filling Material Color	grey
Art. Group	Sealing brushes

Order information

ArtNr	22135310
Commodity code	96035000
Packing Unit	1 Stk./pcs./ud.
PEFC	No
EAN	4017359646366
Country of origin	D

Marketing

Utilizing Industries	Automotive industry | Construction industry | Chemical industry | Electrical engineering | Energy generation | Skilled trades | DIYer | Wood processing | Power plant construction | Plastics industry | Medical equipment industry | Metalworking industry | Pipeline construction | Shipbuilding
Application	Slowing | Sealing | Guiding | Transporting | Cleaning
Application Description	The sealing brush is used for sealing, cleaning, transporting, guiding and slowing.
Article Description Marketing	Sealing brush with straight fittings
On Stock as per Catalogue	No
Catalogue Page	166
Product Description short	Sealing brush, type FH22, with backing height of 22 mm, mixed horse hair filling and backing made of galvanised sheet steel

info@lessmann.com | +49 9082 707-0

Product Description long	The versatile sealing brush can be used for: Sealing, cleaning, dissipating electric charges, transporting, guiding and slowing. The length, height, filling material and type of backing depend on the application. Of premium "Made in Germany" quality, this product is used in most industrial sectors.
Keywords	Automotive industry | Construction industry | Chemical industry | Electrical engineering | Energy generation | Skilled trades | DIYer | Wood processing | Power plant construction | Plastics industry | Medical equipment industry | Metalworking industry | Pipeline construction | Shipbuilding | Slowing | Sealing | Guiding | Cleaning | Transporting | Aluminium | Stainless steel | Wood | Plastic | Copper | Steel | Zinc | Horse hair | ROS | Synthetic filaments | Sealing brush
Processed Surface	Aluminium | Stainless steel | Wood | Plastic | Copper | Zinc

Description

Sealing brushes with straight/angled fittings
Sealing brushes from LESSMANN can be inserted directly via the leg piece so that they can fulfil critical protective functions. They reliably seal doors to protect against draughts, cold air, moisture, leaves and dirt. They also protect moving parts against dust and other unwanted particles. Strip brushes also are suitable for transporting, guiding and slowing sensitive objects.