
DATASHEET

Sealing brush with straight fittings

ArtNr. 23245310

Sealing brushes type FH25 backing width 6 mm holder height 25 mm horsehair mixed ROS/PE (70%/30%) grey - natural/0.15 mm brush backing iron sheet stainless



Characteristics

Technical data

Art. Description ERP	Sealing brushes type FH25 backing width 6 mm holder height 25 mm horsehair mixed ROS/PE (70%/30%) grey - natural/0.15 mm brush backing iron sheet stainless
Brush Overall Length [GL]	variabel mm
Overall Height [GH]	variabel mm
Filling Height [H]	variabel mm
Filling Material Diameter	natur/0.15 mm
Net weight	0.365 kg
Leg Height [FH]	25 mm
Backing Width [RB]	6 mm
Brush Length [L]	variabel mm
Filling Height Visible [HS]	variabel mm
Backing Height [SH]	7.0 mm
Filling material	ROS/PE (70%/30%)
Filling Material Shape	-
Brush Shape	Strip-shaped
Strip Brush Type	Type FH25
Slit Strip Material	Stainless
Filling Material Color	grey
Art. Group	Sealing brushes

Order information

ArtNr	23245310
Commodity code	96035000
Packing Unit	1 Stk./pcs./ud.
EAN	4017359648544
PEFC	No
Country of origin	D

Marketing

Utilizing Industries	Automotive industry | Construction industry | Chemical industry | Electrical engineering | Energy generation | Skilled trades | DIYer | Wood processing | Power plant construction | Plastics industry | Medical equipment industry | Metalworking industry | Pipeline construction | Shipbuilding
Application	Slowing | Sealing | Guiding | Transporting | Cleaning
Application Description	The sealing brush is used for sealing, cleaning, transporting, guiding and slowing.
Article Description Marketing	Sealing brush with straight fittings
On Stock as per Catalogue	No
Catalogue Page	166
Product Description short	Sealing brush, type FH25, with backing height of 25 mm, mixed horse hair filling and backing made of stainless sheet steel

Product Description long	The versatile sealing brush can be used for: Sealing, cleaning, dissipating electric charges, transporting, guiding and slowing. The length, height, filling material and type of backing depend on the application. Of premium "Made in Germany" quality, this product is used in most industrial sectors.
Keywords	Automotive industry | Construction industry | Chemical industry | Electrical engineering | Energy generation | Skilled trades | DIYer | Wood processing | Power plant construction | Plastics industry | Medical equipment industry | Metalworking industry | Pipeline construction | Shipbuilding | Slowing | Sealing | Guiding | Cleaning | Transporting | Aluminium | Stainless steel | Wood | Plastic | Copper | Steel | Zinc | Horse hair | ROS | Synthetic filaments | Sealing brush
Processed Surface	Aluminium | Stainless steel | Wood | Plastic | Copper | Zinc

Description

Sealing brushes with straight/angled fittings
Sealing brushes from LESSMANN can be inserted directly via the leg piece so that they can fulfil critical protective functions. They reliably seal doors to protect against draughts, cold air, moisture, leaves and dirt. They also protect moving parts against dust and other unwanted particles. Strip brushes also are suitable for transporting, guiding and slowing sensitive objects.