LESSMANN®
THE GERMAN BRUSH COMPANY


DATASHEET

Single segment brush



ArtNr. 320841

Single segment brushes RBE dia 100 x 13-17 mm EBD 12 mm tube 30 mm abrasive nylon SIC PA 6 crimped K120 / 0.60 mm bore 12 mm trim length 20 mm



Characteristics

Technical data

Art. Description ERP	Single segment brushes RBE dia 100 x 13-17 mm EBD 12 mm tube 30 mm abrasive nylon SIC PA 6 crimped K120 / 0.60 mm bore 12 mm trim length 20 mm
Filling Height [H]	20 mm
Grit	K120
Filling Material Diameter	0.60 mm
Bore Diameter [DB]	12 mm
Net weight	0.11 kg
Filling Width [A]	13-17 mm
Number of Rows [RZ]	1
Clamping Width Cover Disc [EBD]	12 mm
Tube Diameter [R]	30 mm
RPM max.	8000
Brush Diameter [D]	100 mm
Bore Diameter Maximum [DBmax]	20 mm
Bore Diameter Minimum [DBmin]	12 mm
Clamping Width Tube [EB]	0 in
Clamping Width Tube [EB]	2.4 mm
Filling material	SIC PA6
Filling Material Shape	Crimped
Art. Group	Single segment brushes RBE

Order information

ArtNr	320841
EAN	4017359163825
Commodity code	96035000
Packing Unit	5 Stk./pcs./ud.
PEFC	No
Country of origin	D

Marketing

Utilizing Industries	Automotive industry | Skilled trades | Metalworking industry
Application	Deburring | Rounding edges | Polishing | Cleaning | Grinding | Structuring
Application Description	The single segment brush is used for deburring, rounding edges, grinding, cleaning, polishing and structuring.
Article Description Marketing	Single segment brush
On Stock as per Catalogue	Yes
Catalogue Page	29
Product Description short	Single segment brush with a diameter of 100 mm, bore diameter of 12 mm and 120-grit silicon carbide bristles
Product Description long	The single segment brush is used for deburring, rounding edges, grinding, cleaning, polishing and structuring surfaces. Its high-quality silicon carbide bristles meet these requirements. Of premium "Made in Germany" quality, this product is frequently used in industrial companies and the skilled trades for metalworking and in the automotive supply sector.

info@lessmann.com | +49 9082 707-0

Keywords	Automotive industry | Skilled trades | Metalworking industry | Deburring | Rounding edges | Polishing | Cleaning | Grinding | Structuring | Aluminium | Stainless steel | Steel | Abrasive filaments | SIC | Single segment brush | bore
Processed Surface	Aluminium | Stainless steel

Description

Single segment brushes
Single segment brushes from LESSMANN typically have a small clamping width and narrower filling width. They are used mainly for deburring work in stationary machines or machining centres. The design of these brushes makes it possible for them to be assembled into wide rollers.