


Single segment brush



ArtNr. 331161

Single segment brushes RBE dia 125 x 16-20 mm EBD 12 mm tube 40 mm steel wire STA crimped 0.30 mm bore 12 mm trim length 29 mm



Characteristics

Technical data

Art. Description ERP	Single segment brushes RBE dia 125 x 16-20 mm EBD 12 mm tube 40 mm steel wire STA crimped 0.30 mm bore 12 mm trim length 29 mm
Filling Height [H]	29 mm
Filling Material Diameter	0.30 mm
Bore Diameter [DB]	12 mm
Net weight	0.222 kg
Filling Width [A]	16-20 mm
Number of Rows [RZ]	1
Clamping Width Cover Disc [EBD]	12 mm
Tube Diameter [R]	40 mm
RPM max.	12500
Brush Diameter [D]	125 mm
Bore Diameter Maximum [DBmax]	25 mm
Bore Diameter Minimum [DBmin]	12 mm
Clamping Width Tube [EB]	0 in
Clamping Width Tube [EB]	2.4 mm
Filling material	STA
Filling Material Shape	Crimped
Art. Group	Single segment brushes RBE

Order information

ArtNr	331161
EAN	4017359379677
Commodity code	96035000
Packing Unit	5 Stk./pcs./ud.
PEFC	No
Country of origin	D

Marketing

Utilizing Industries	Automotive industry Skilled trades Metalworking industry
Application	Removing heat discolouration Deburring Removing paint Derusting Cleaning Weld seam finishing
Application Description	The single segment brush is used for removing heat discolouration, cleaning welds, derusting, removing paint and deburring.
Article Description Marketing	Single segment brush
On Stock as per Catalogue	No
Catalogue Page	30
Product Description short	Single segment brush with a diameter of 125 mm, bore diameter of 12 mm and steel wire filling

Product Description long

The single segment brush is used to remove rust, paint, etc. and to clean welds. It can be used for light deburring work and to remove the heat discolouration caused by welding stainless steel. The steel filling is suitable for steel surfaces. The brush, with its crimped wire and dense filling, ensures smooth and accurate rotary motion. Of premium "Made in Germany" quality, this product is frequently used in industrial companies and the skilled trades for metalworking and in the automotive supply sector.

Keywords

Automotive industry | Skilled trades | Metalworking industry | Removing heat discolouration | Deburring | Removing paint | Derusting | Cleaning | Weld seam finishing | Steel | Steel wire | STA | Single segment brush | bore

Processed Surface

Steel

Description

Single segment brushes

Single segment brushes from LESSMANN typically have a small clamping width and narrower filling width. They are used mainly for deburring work in stationary machines or machining centres. The design of these brushes makes it possible for them to be assembled into wide rollers.