LESSMANN®
THE GERMAN BRUSH COMPANY


DATASHEET

Single segment brush



ArtNr. 340C31

Single segment brushes RBE dia 150 x 14-19 mm EBD 14 mm tube 50 mm abrasive nylon KK PA6.12 crimped K120 / 1.10 mm bore 12 mm trim length 32.5 mm



Characteristics

Technical data

Art. Description ERP	Single segment brushes RBE dia 150 x 14-19 mm EBD 14 mm tube 50 mm abrasive nylon KK PA6.12 crimped K120 / 1.10 mm bore 12 mm trim length 32.5 mm
Grit	K120
Filling Material Diameter	1.10 mm
Bore Diameter [DB]	12 mm
Net weight	0.26 kg
Filling Width [A]	14-19 mm
Number of Rows [RZ]	1
Clamping Width Cover Disc [EBD]	14 mm
Tube Diameter [R]	50 mm
RPM max.	6000
Brush Diameter [D]	150 mm
Filling Height [H]	32.5 mm
Bore Diameter Maximum [DBmax]	30 mm
Bore Diameter Minimum [DBmin]	12 mm
Clamping Width Tube [EB]	0 in
Clamping Width Tube [EB]	2.4 mm
Filling material	KK PA6.12
Filling Material Shape	Crimped
Art. Group	Single segment brushes RBE

Order information

ArtNr	340C31
EAN	4017359673430
Commodity code	96035000
Packing Unit	5 Stk./pcs./ud.
PEFC	No
Country of origin	D

Marketing

Utilizing Industries	Automotive industry | Skilled trades | Metalworking industry
Application	Deburring | Rounding edges | Polishing | Cleaning | Grinding | Structuring
Application Description	The single segment brush is used for deburring, rounding edges, grinding, cleaning, polishing and structuring.
Article Description Marketing	Single segment brush
On Stock as per Catalogue	Yes
Catalogue Page	29
Product Description short	Single segment brush with a diameter of 150 mm, bore diameter of 12 mm and 120-grit abrasive filaments with ceramic grit

Product Description long	The single segment brush is used for deburring, rounding edges, grinding, cleaning, polishing and structuring surfaces. Its high-quality abrasive filaments with ceramic grit meet these requirements. Of premium "Made in Germany" quality, this product is frequently used in industrial companies and the skilled trades for metalworking and in the automotive supply sector.
Keywords	Automotive industry | Skilled trades | Metalworking industry | Deburring | Rounding edges | Polishing | Cleaning | Grinding | Structuring | Stainless steel | NF metals, hard | Steel | Abrasive filaments | Ceramic grit | Single segment brush | bore
Processed Surface	Stainless steel | NF metals, hard | Steel

Description

Single segment brushes
Single segment brushes from LESSMANN typically have a small clamping width and narrower filling width. They are used mainly for deburring work in stationary machines or machining centres. The design of these brushes makes it possible for them to be assembled into wide rollers.