
DATASHEET

Single segment brush

ArtNr. 362272

Single segment brushes RBE dia 200 x 21-25 mm EBD 20 mm tube 80 mm steel wire STH crimped 0.35 mm bore 16 mm trim length 42.5 mm



Characteristics

Technical data

Art. Description ERP	Single segment brushes RBE dia 200 x 21-25 mm EBD 20 mm tube 80 mm steel wire STH crimped 0.35 mm bore 16 mm trim length 42.5 mm
Net weight	1.064 kg
Filling Height [H]	42.5 mm
Brush Diameter [D]	200 mm
Filling Material Diameter	0.35 mm
Bore Diameter [DB]	16 mm
Filling Width [A]	21-25 mm
Number of Rows [RZ]	1
Bore Diameter Maximum [DBmax]	60 mm
Bore Diameter Minimum [DBmin]	16 mm
RPM max.	4500
Clamping Width Cover Disc [EBD]	20 mm
Tube Diameter [R]	80 mm
Clamping Width Tube [EB]	0 in
Clamping Width Tube [EB]	3 mm
Filling material	STH
Filling Material Shape	Crimped
Art. Group	Single segment brushes RBE

Order information

ArtNr	362272
EAN	4017359304440
Commodity code	96035000
Packing Unit	5 Stk./pcs./ud.
PEFC	No
Country of origin	D

Marketing

Utilizing Industries	Automotive industry | Skilled trades | Metalworking industry
Application	Removing heat discolouration | Deburring | Removing paint | Derusting | Cleaning | Weld seam finishing
Application Description	The single segment brush is used for removing heat discolouration, cleaning welds, derusting, removing paint and deburring.
Article Description Marketing	Single segment brush
On Stock as per Catalogue	No
Catalogue Page	30
Product Description short	Single segment brush with a diameter of 200 mm, bore diameter of 16 mm and steel wire filling

info@lessmann.com | +49 9082 707-0

Product Description long	The single segment brush is used to remove rust, paint, etc. and to clean welds. It can be used for light deburring work and to remove the heat discolouration caused by welding stainless steel. The steel filling is suitable for steel surfaces. The brush, with its crimped wire and dense filling, ensures smooth and accurate rotary motion. Of premium "Made in Germany" quality, this product is frequently used in industrial companies and the skilled trades for metalworking and in the automotive supply sector.
Keywords	Automotive industry | Skilled trades | Metalworking industry | Removing heat discolouration | Deburring | Removing paint | Derusting | Cleaning | Weld seam finishing | Steel | Steel wire | High-tensile wire | STH | Single segment brush | bore
Processed Surface	Steel

Description

Single segment brushes
Single segment brushes from LESSMANN typically have a small clamping width and narrower filling width. They are used mainly for deburring work in stationary machines or machining centres. The design of these brushes makes it possible for them to be assembled into wide rollers.