LESSMANN®
THE GERMAN BRUSH COMPANY

DATASHEET

Single segment brush

ArtNr. 372851

Single segment brushes RBE dia 250 x 17-21 mm EBD 19 mm tube 150 mm abrasive nylon SIC PA 6 crimped K180 / 1.00 mm bore 25.4 mm trim length 30 mm



Characteristics

Technical data

Art. Description ERP	Single segment brushes RBE dia 250 x 17-21 mm EBD 19 mm tube 150 mm abrasive nylon SIC PA 6 crimped K180 / 1.00 mm bore 25.4 mm trim length 30 mm
Grit	K180
Filling Material Diameter	1.00 mm
Bore Diameter [DB]	25.4 mm
Net weight	1.324 kg
Filling Width [A]	17-21 mm
Number of Rows [RZ]	1
Clamping Width Cover Disc [EBD]	19 mm
Tube Diameter [R]	150 mm
RPM max.	3600
Brush Diameter [D]	250 mm
Filling Height [H]	30 mm
Bore Diameter Maximum [DBmax]	130 mm
Bore Diameter Minimum [DBmin]	25.4 mm
Clamping Width Tube [EB]	0 in
Clamping Width Tube [EB]	3 mm
Filling material	SIC PA6
Filling Material Shape	Crimped
Art. Group	Single segment brushes RBE

Order information

ArtNr	372851
EAN	4017359309162
Commodity code	96035000
Packing Unit	5 Stk./pcs./ud.
PEFC	No
Country of origin	D

Marketing

Utilizing Industries	Automotive industry | Skilled trades | Metalworking industry
Application	Deburring | Rounding edges | Polishing | Cleaning | Grinding | Structuring
Application Description	The single segment brush is used for deburring, rounding edges, grinding, cleaning, polishing and structuring.
Article Description Marketing	Single segment brush
On Stock as per Catalogue	No
Catalogue Page	29
Product Description short	Single segment brush with a diameter of 250 mm, bore diameter of 25.4 mm and 180-grit silicon carbide bristles
Product Description long	The single segment brush is used for deburring, rounding edges, grinding, cleaning, polishing and structuring surfaces. Its high-quality silicon carbide bristles meet these requirements. Of premium "Made in Germany" quality, this product is frequently used in industrial companies and the skilled trades for metalworking and in the automotive supply sector.

Keywords	Automotive industry | Skilled trades | Metalworking industry | Deburring | Rounding edges | Polishing | Cleaning | Grinding | Structuring | Aluminium | Stainless steel | Steel | Abrasive filaments | SIC | Single segment brush | bore
Processed Surface	Aluminium | Stainless steel

Description

Single segment brushes
Single segment brushes from LESSMANN typically have a small clamping width and narrower filling width. They are used mainly for deburring work in stationary machines or machining centres. The design of these brushes makes it possible for them to be assembled into wide rollers.