


Deburring wheel brush



ArtNr. 37709100

Deburring brushes ERB dia 250 x 55-60 mm EBR 55 mm
 EBA 58 mm tube 100 mm steel wire stainless ROF/SIC
 PA6.12 crimped K120 / 0.20/0.60 mm bore 100+ mm trim
 length 50 mm



Characteristics

Technical data

Art. Description ERP	Deburring brushes ERB dia 250 x 55-60 mm EBR 55 mm EBA 58 mm tube 100 mm steel wire stainless ROF/SIC PA6.12 crimped K120 / 0.20/0.60 mm bore 100+ mm trim length 50 mm
Grit	K120
Filling Material Diameter	0.20/0.60 mm
Bore Diameter [DB]	100+ mm
Net weight	2.066 kg
Filling Width [A]	55-60 mm
Number of Rows [RZ]	4
Clamping Width Tubular Rivet [EBR]	55 mm
Clamping Width Metal Disc [EBA]	58 mm
Tube Diameter [R]	100 mm
RPM max.	3600
Brush Diameter [D]	250 mm
Filling Height [H]	50 mm
Filling material	ROF/SIC PA6.12
Filling Material Shape	Crimped
Art. Group	Deburring brushes ERB

Order information

ArtNr	37709100
EAN	4017359277355
Commodity code	96035000
Packing Unit	1 Stk./pcs./ud.
PEFC	No
Country of origin	D

Marketing

Utilizing Industries	Automotive industry Skilled trades Metalworking industry
Application	Deburring Rounding edges Polishing Cleaning Wire stripping Roughening Removing paint Derusting
Application Description	The deburring wheel brush is used for deburring, rounding edges, roughening, stripping and polishing, removing rust or paint, and cleaning.
Article Description Marketing	Deburring wheel brush
On Stock as per Catalogue	No
Catalogue Page	51
Product Description short	Deburring wheel brush, 55-60 mm wide, with a diameter of 250 mm, and mixed filaments of stainless steel wire and 120-grit silicon carbide bristles

Product Description long

The deburring wheel brush is mainly used for deburring work in stationary machines, tabletop deburring machines and machining centres. The version with stainless steel wire is used on stainless steel and aluminium surfaces. This wheel brush is suitable for the following applications: Removing rust, paint, dirt, etc., and for roughening, deburring, stripping and polishing. The special brush has a high wire content, extremely uniform distribution of filaments, and every single brush is tested. What is more, these brushes have a longer service life thanks to the premium grade wire used. All brushes are fitted with a double keyway. Of premium "Made in Germany" quality, this product is frequently used in industrial companies and the skilled trades for metalworking and in the automotive supply sector.

Keywords

Automotive industry | Skilled trades | Metalworking industry | Wire stripping | Roughening | Deburring | Removing paint | Derusting | Rounding edges | Polishing | Cleaning | Aluminium | Stainless steel | Copper | Steel | Titanium | Zinc | Mixed filaments | Stainless steel wire | Abrasive filaments | SIC | Deburring wheel brush

Processed Surface

Aluminium | Stainless steel | Copper | Titanium | Zinc

Description

Deburring wheel brushes

These brushes are used mainly for deburring work in stationary machines, in tabletop deburring machines and machining centres.