LESSMANN®
THE GERMAN BRUSH COMPANY


DATASHEET

Crimped wheel brush



ArtNr. 377164

Wheel brushes RB dia 250 x 55-60 mm EBR 46 mm EBA 49 mm tube 100 mm steel wire STA crimped 0.30 mm bore 50.8DKN mm 13x7 mm adaptor set Ø50.8+DKN/ Ø30/1" /22.2/20/16/ Ø1/2"/12 trim length 50 mm



Characteristics

Technical data

Art. Description ERP	Wheel brushes RB dia 250 x 55-60 mm EBR 46 mm EBA 49 mm tube 100 mm steel wire STA crimped 0.30 mm bore 50.8DKN mm 13x7 mm adaptor set Ø50.8+DKN/ Ø30/1"/22.2/20/16/ Ø1/2"/12 trim length 50 mm
Filling Material Diameter	0.30 mm
Bore Diameter [DB]	50.8DKN mm
Net weight	2.841 kg
Filling Width [A]	55-60 mm
Number of Rows [RZ]	4
Double Keyway [DKN]	13x7
Tube Adapter Set [RED]	Ø50.8+DKN/ Ø30/1"/22.2/20/16/ Ø1/2"/12
Tube Diameter [R]	100 mm
RPM max.	3600
Brush Diameter [D]	250 mm
Filling Height [H]	50 mm
Clamping Width Tubular Rivet [EBR]	46 mm
Bore Diameter Maximum [DBmax]	100 mm
Bore Diameter Minimum [DBmin]	20 mm
Clamping Width Metal Disc [EBA]	49 mm
Filling material	STA
Filling Material Shape	Crimped
Art. Group	Wheel brushes RB

Order information

ArtNr	377164
EAN	4017359005422
Commodity code	96035000
Packing Unit	1 Stk./pcs./ud.
PEFC	No
Country of origin	D

Marketing

Utilizing Industries	Automotive industry | Construction industry | Chemical industry | Skilled trades | Plastics industry | Medical equipment industry | Metalworking industry
Application	Wire stripping | Roughening | Deburring | Removing paint | Derusting | Polishing | Cleaning
Application Description	The wheel brush is used for deburring, roughening, stripping, polishing, cleaning, and removing rust and paint.
Article Description Marketing	Crimped wheel brush
On Stock as per Catalogue	Yes
Catalogue Page	33
Product Description short	Wheel brush with a diameter of 250 mm, bore diameter of 50.8 mm, double keyway, adapter sets 4 and 1 and steel wire filling

Product Description long	The wheel brush is mainly used for deburring work in stationary machines or machining centres. The version with steel wire is used on steel surfaces. This wheel brush is suitable for the following applications: Removing rust, paint, dirt, etc., and for roughening, deburring, stripping and polishing. The wire and tube diameters are determining factors for choosing the right article. The version with a large tube diameter (dimension R) contains more wire, offers harder action, and has a longer service life. Of premium "Made in Germany" quality, this product is frequently used in industrial companies and the skilled trades for metalworking, in automotive supply and construction firms, as well as in the plastics, rubber, chemical and medical equipment industries.
Keywords	Automotive industry | Construction industry | Chemical industry | Skilled trades | Plastics industry | Medical equipment industry | Metalworking industry | Wire stripping | Roughening | Deburring | Removing paint | Derusting | Polishing | Cleaning | Steel | Steel wire | STA | Wheel brushes | Crimped | bore
Processed Surface	Steel

Description

Wheel brushes
Wheel brushes from LESSMANN are used for a variety of purposes in surface finishing. They are ideal for removing rust, paint, or dirt, and for roughening, deburring, stripping and polishing.