
LESSMANN®
THE GERMAN BRUSH COMPANY

DATASHEET

Deburring wheel brush

ArtNr. 377C55

Deburring brushes ERB dia 250 x 50-55 mm EBR 55 mm EBA 58 mm tube 100 mm abrasive nylon KK PA6.12 crimped K180 / 1.00 mm bore 50.8DKN mm 13x7 mm trim length 50 mm



Characteristics

Technical data

Filling Height [H]	50 mm
Brush Diameter [D]	250 mm
Grit	K180
Filling Material Diameter	1.00 mm
Filling material	KK PA6.12
Filling Material Shape	Crimped
Bore Diameter [DB]	50.8DKN mm
Net weight	0.001 kg
Art. Description ERP	Deburring brushes ERB dia 250 x 50-55 mm EBR 55 mm EBA 58 mm tube 100 mm abrasive nylon KK PA6.12 crimped K180 / 1.00 mm bore 50.8DKN mm 13x7 mm trim length 50 mm
Filling Width [A]	50-55 mm
Number of Rows [RZ]	4
RPM max.	3600
Clamping Width Tubular Rivet [EBR]	55 mm
Double Keyway [DKN]	13x7
Clamping Width Metal Disc [EBA]	58 mm
Tube Diameter [R]	100 mm
Art. Group	Deburring brushes ERB

Order information

ArtNr	377C55
Packing Unit	1 Stk./pcs./ud.
EAN	4017359798492
Country of origin	D
Commodity code	96035000
PEFC	No

Marketing

Utilizing Industries	Automotive industry | Skilled trades | Metalworking industry
Application	Wire stripping | Roughening | Deburring | Removing paint | Derusting | Rounding edges | Polishing | Cleaning | Grinding | Structuring
Application Description	The deburring wheel brush is used for deburring, rounding edges, roughening, stripping and polishing, removing rust or paint, and cleaning.
Article Description Marketing	Deburring wheel brush
On Stock as per Catalogue	No
Catalogue Page	51
Product Description short	Deburring wheel brush, 50 mm wide, with a diameter of 250 mm, double keyway and 180-grit abrasive filaments with ceramic grit

info@lessmann.com | +49 9082 707-0

Product Description long	The deburring wheel brush is mainly used for deburring work in stationary machines, tabletop deburring machines and machining centres. The version with ceramic grit is used on stainless steel and aluminium surfaces. The aggressiveness is: hard. This wheel brush is suitable for the following applications: Removing rust, paint, dirt, etc. and for roughening, deburring, rounding edges, stripping and polishing. The special brush has a high wire content, extremely uniform distribution of filaments, and every single brush is tested. What is more, these brushes have a longer service life thanks to the premium grade wire used. All brushes are fitted with a double keyway. Of premium "Made in Germany" quality, this product is frequently used in industrial companies and the skilled trades for metalworking and in the automotive supply sector.
Processed Surface	Stainless steel | NF metals, hard | Steel

info@lessmann.com | +49 9082 707-0