LESSMANN®
THE GERMAN BRUSH COMPANY

DATASHEET

# Crimped wheel brush with shank

## ArtNr. 414193

Wheel brushes SRB with 6 x 30 mm shank dia 40 x 12 mm steel wire STA crimped 0.50 mm trim length 9 mm




## Characteristics

### Technical data

| | |
|---|---|
| Art. Description ERP | Wheel brushes SRB with 6 x 30 mm shank dia 40 x 12 mm steel wire STA crimped 0.50 mm trim length 9 mm |
| Overall Height [GH] | 46 mm |
| Filling Material Diameter | 0.50 mm |
| Net weight | 0.068 kg |
| Filling Width [A] | 12 mm |
| Number of Rows [RZ] | 3 |
| Shank Diameter [SD] | 6 mm |
| Tube Diameter [R] | 8 mm |
| Shank Length [LS] | 30 mm |
| RPM max. | 18000 |
| Brush Diameter [D] | 40 mm |
| Filling Height [H] | 9 mm |
| Filling material | STA |
| Filling Material Shape | Crimped |
| Art. Group | Wheel brushes SRB |

### Order information

| | |
|---|---|
| ArtNr | 414193 |
| EAN | 4017359205099 |
| Commodity code | 96035000 |
| Packing Unit | 10 Stk./pcs./ud. |
| PEFC | No |
| Country of origin | D |

### Marketing

| | |
|---|---|
| Utilizing Industries | Automotive industry \| Construction industry \| Skilled trades \| Metalworking industry |
| Application | Deburring \| Removing paint \| Derusting \| Cleaning \| Weld seam finishing \| Structuring |
| Application Description | The wheel brush is used for cleaning welds, derusting, removing paint, deburring and structuring. |
| Article Description Marketing | Crimped wheel brush with shank |
| On Stock as per Catalogue | No |
| Catalogue Page | 78 |
| Product Description short | Wheel brush with a diameter of 40 mm, shank diameter of 6 mm and steel wire filling |


info@lessmann.com | +49 9082 707-0

| | |
|---|---|
| Product Description long | The wheel brush is used to remove rust, paint, etc., clean welds and for light deburring work. The brush can be mounted in hand-operated grinders and flexible shafts. The steel filling is suitable for steel surfaces. The wheel brush, with its integrated 6 mm shank, is suitable for professional use. The dense wire filling and perfectly balanced running properties are characteristic of this product. Of premium "Made in Germany" quality, this product is primarily used in factories and the skilled trades for metalworking, in car repair shops, and in stair, railing and container construction. |
| Keywords | Automotive industry \| Construction industry \| Skilled trades \| Metalworking industry \| Deburring \| Removing paint \| Derusting \| Cleaning \| Weld seam finishing \| Structuring \| Steel \| Steel wire \| STA \| Wheel brushes \| Crimped \| Shank |
| Processed Surface | Steel \| Cast iron |

## Description

**Wheel brushes with shank**
Wheel brushes with shank from LESSMANN are ideal for removing rust, paint and dirt, cleaning welds, and light deburring work. The integrated shank, dense filling and perfectly balanced running properties are characteristic of this all-round tool. Hard-to-reach areas can be processed more easily by mounting brushes of this type in hand-operated grinders or flexible shafts.