LESSMANN®
THE GERMAN BRUSH COMPANY

DATASHEET

Crimped wheel brush with shank, encapsulated

ArtNr. 415160

Wheel brushes encapsulated SRBKG red with 6 x 30 mm shank dia 50 x 8 mm steel wire STA crimped 0.30 mm trim length 12 mm



Characteristics

Technical data

Art. Description ERP	Wheel brushes encapsulated SRBKG red with 6 x 30 mm shank dia 50 x 8 mm steel wire STA crimped 0.30 mm trim length 12 mm
Overall Height [GH]	46 mm
Filling Material Diameter	0.30 mm
Net weight	0.056 kg
Filling Width [A]	8 mm
Shank Diameter [SD]	6 mm
Tube Diameter [R]	10 mm
Shank Length [LS]	30 mm
RPM max.	15000
Shore Hardness	80-85
Brush Diameter [D]	50 mm
Filling Height [H]	12 mm
Number of Rows [RZ]	1
Filling material	STA
Filling Material Shape	Crimped
Filling Material Color	red
Art. Group	Wheel brushes, encapsulated SRBKG

Order information

ArtNr	415160
EAN	4017359009314
Commodity code	96035000
Packing Unit	10 Stk./pcs./ud.
PEFC	No
Country of origin	D

Marketing

Utilizing Industries	Automotive industry | Construction industry | Skilled trades | Metalworking industry
Application	Deburring | Removing paint | Derusting | Cleaning | Weld seam finishing
Application Description	The wheel brush is used for derusting, removing paint and cleaning welds.
Article Description Marketing	Crimped wheel brush with shank, encapsulated
On Stock as per Catalogue	Yes
Version	Encapsulated
Catalogue Page	77
Product Description short	Wheel brush with a diameter of 50 mm, shank diameter of 6 mm and encapsulated steel wire filling

info@lessmann.com | +49 9082 707-0

Product Description long	The wheel brush is used to remove rust, paint, etc. and to clean welds. The brush can be mounted in hand-operated grinders and flexible shafts. The steel filling is suitable for steel surfaces. The aggressiveness is: hard. With its permanently mounted 6 mm shank, it is suitable for professional use. The dense wire filling and perfectly balanced running properties are characteristic of this all-round tool. In this encapsulated brush, the steel wire filling is embedded in a tough polymer compound. The filling width remains constant during use as a result, and encapsulation prevents premature breakage of individual wires. Of premium "Made in Germany" quality, this product is primarily used in factories and the skilled trades for metalworking, in car repair shops, and in stair, railing and container construction.
Keywords	Automotive industry | Construction industry | Skilled trades | Metalworking industry | Deburring | Removing paint | Derusting | Cleaning | Weld seam finishing | Steel | Steel wire | STA | Encapsulated | Wheel brushes | Crimped | Shank
Processed Surface	Steel | Cast iron

Description

Wheel brushes with shank
Wheel brushes with shank from LESSMANN are ideal for removing rust, paint and dirt, cleaning welds, and light deburring work. The integrated shank, dense filling and perfectly balanced running properties are characteristic of this all-round tool. Hard-to-reach areas can be processed more easily by mounting brushes of this type in hand-operated grinders or flexible shafts.