LESSMANN®
THE GERMAN BRUSH COMPANY


DATASHEET

Crimped wheel brush with shank



ArtNr. 415872EP

Wheel brushes SRBK with 6 x 30 mm shank dia 50 x 10 mm abrasive nylon SIC PA 6 crimped K320 / 0.60 mm trim length 12.5 mm single pack



Characteristics

Technical data

Overall Height [GH]	46 mm
Filling Height [H]	12.5 mm
Brush Diameter [D]	50 mm
Grit	K320
Filling Material Diameter	0.60 mm
Filling material	SIC PA6
Filling Material Shape	Crimped
Net weight	0.001 kg
Art. Description ERP	Wheel brushes SRBK with 6 x 30 mm shank dia 50 x 10 mm abrasive nylon SIC PA 6 crimped K320 / 0.60 mm trim length 12.5 mm single pack
Filling Width [A]	10 mm
Number of Rows [RZ]	2
RPM max.	15000
Shank Diameter [SD]	6 mm
Tube Diameter [R]	10 mm
Art. Group	Wheel brushes SRBK
Shank Length [LS]	30 mm

Order information

ArtNr	415872EP
Packing Unit	1 Stk./pcs./ud.
EAN	4017359833544
Seconday Packing Unit	10 Stk./pcs./ud.
Country of origin	D
Commodity code	96035000
PEFC	No

Marketing

Utilizing Industries	Automotive industry | Construction industry | Skilled trades | Metalworking industry
Application	Deburring | Removing paint | Derusting | Cleaning | Weld seam finishing | Structuring | Rounding edges | Polishing | Grinding
Application Description	The wheel brush is used for cleaning welds, derusting, removing paint, deburring and structuring.
Article Description Marketing	Crimped wheel brush with shank
On Stock as per Catalogue	No
Catalogue Page	142
Product Description short	Wheel brush with a diameter of 40 mm, shank diameter of 6 mm and steel wire filling

info@lessmann.com | +49 9082 707-0

Product Description long	The wheel brush is used to remove rust, paint, etc., clean welds and for light deburring work. The brush can be mounted in hand-operated grinders and flexible shafts. The steel filling is suitable for steel surfaces. The aggressiveness is: soft. The wheel brush, with its integrated 6 mm shank, is suitable for professional use. The dense wire filling and perfectly balanced running properties are characteristic of this product. Of premium "Made in Germany" quality, this product is primarily used in factories and the skilled trades for metalworking, in car repair shops, and in stair, railing and container construction.
Processed Surface	Titanium | Cast iron | Aluminium | Stainless steel | Plastic