LESSMANN®
THE GERMAN BRUSH COMPANY


DATASHEET

Crimped wheel brush with shank



ArtNr. 416160EP

Wheel brushes encapsulated SRBKG red with 6 x 30 mm shank dia 60 x 8 mm steel wire STA crimped 0.30 mm trim length 17 mm single pack



Characteristics

Technical data

Overall Height [GH]	46 mm
Filling Height [H]	17 mm
Brush Diameter [D]	60 mm
Filling Material Diameter	0.30 mm
Filling material	STA
Filling Material Shape	Crimped
Net weight	0.086 kg
Art. Description ERP	Wheel brushes encapsulated SRBKG red with 6 x 30 mm shank dia 60 x 8 mm steel wire STA crimped 0.30 mm trim length 17 mm single pack
Filling Width [A]	8 mm
Number of Rows [RZ]	1
RPM max.	15000
Shore Hardness	80-85
Shank Diameter [SD]	6 mm
Filling Material Color	red
Tube Diameter [R]	10 mm
Art. Group	Wheel brushes, encapsulated SRBKG
Shank Length [LS]	30 mm

Order information

ArtNr	416160EP
Packing Unit	1 Stk./pcs./ud.
EAN	4017359833995
Seconday Packing Unit	10 Stk./pcs./ud.
Country of origin	D
Commodity code	96035000
PEFC	No

Marketing

Utilizing Industries	Automotive industry | Construction industry | Skilled trades | Metalworking industry
Application	Deburring | Removing paint | Derusting | Cleaning | Weld seam finishing | Structuring
Application Description	The wheel brush is used for cleaning welds, derusting, removing paint, deburring and structuring.
Article Description Marketing	Crimped wheel brush with shank
On Stock as per Catalogue	Yes
Catalogue Page	142
Product Description short	Wheel brush with a diameter of 100 mm, shank diameter of 6 mm and steel wire filling

Product Description long	The wheel brush is used to remove rust, paint, etc., clean welds and for light deburring work. The brush can be mounted in hand-operated grinders and flexible shafts. The steel filling is suitable for steel surfaces. The wheel brush, with its integrated 6 mm shank, is suitable for professional use. The dense wire filling and perfectly balanced running properties are characteristic of this product. Of premium "Made in Germany" quality, this product is primarily used in factories and the skilled trades for metalworking, in car repair shops, and in stair, railing and container construction.
Processed Surface	Titanium | Cast iron | Steel

info@lessmann.com | +49 9082 707-0