LESSMANN®
THE GERMAN BRUSH COMPANY

DATASHEET

Wheel brush with shank



ArtNr. 41784K

Wheel brushes SRBK with 6 x 30 mm shank dia 70 x 10 mm abrasive nylon SIC PA 6 crimped K120 / 1.10 mm trim length 19 mm frontal side plate with plastic



Characteristics

Technical data

Overall Height [GH]	46 mm
Filling Height [H]	19 mm
Brush Diameter [D]	70 mm
Grit	K120
Filling Material Diameter	1.10 mm
Filling material	SIC PA6
Filling Material Shape	Crimped
Net weight	0.047 kg
Art. Description ERP	Wheel brushes SRBK with 6 x 30 mm shank dia 70 x 10 mm abrasive nylon SIC PA 6 crimped K120 / 1.10 mm trim length 19 mm frontal side plate with plastic
Filling Width [A]	10 mm
Number of Rows [RZ]	2
RPM max.	15000
Shank Diameter [SD]	6 mm
Tube Diameter [R]	10 mm
Art. Group	Wheel brushes SRBK
Shank Length [LS]	30 mm

Order information

ArtNr	41784K
Packing Unit	10 Stk./pcs./ud.
EAN	4017359818268
Seconday Packing Unit	0 Stk./pcs./ud.
Country of origin	D
Commodity code	96035000
PEFC	No

Marketing

Utilizing Industries	Automotive industry | Construction industry | Skilled trades | Metalworking industry
Application	Deburring | Rounding edges | Polishing | Cleaning | Grinding | Structuring
Application Description	The wheel brush is used for deburring, rounding edges, grinding, polishing, structuring and cleaning.
Article Description Marketing	Wheel brush with shank
On Stock as per Catalogue	Yes
Catalogue Page	81
Product Description short	Wheel brush with a diameter of 70 mm, shank diameter of 6 mm, 120-grit silicon carbide bristles and plastic side plate

info@lessmann.com | +49 9082 707-0

Product Description long	The wheel brush is suitable for deburring, rounding edges, polishing and structuring stainless steel, aluminium and plastic in hand-operated grinders or flexible shafts. Its high-quality silicon carbide bristles meet these special requirements. Material removal from the workpiece is abrasive; the aggressiveness is: coarse. It can be used for light deburring work. The wheel brush, with its integrated 6 mm shank, is suitable for professional use. The dense filling and perfectly balanced running properties are characteristic of this all-round tool. Of premium "Made in Germany" quality, this product is primarily used in factories and the skilled trades for metalworking, in car repair shops, and in stair, railing and container construction. The plastic side plate prevents damage if contact is made with the workpiece.
Keywords	Automotive industry | Construction industry | Skilled trades | Metalworking industry | Deburring | Rounding edges | Polishing | Cleaning | Grinding | Structuring | Aluminium | Stainless steel | Plastic | Steel | Abrasive filaments | SIC | Wheel brushes | Shank
Processed Surface	Aluminium | Stainless steel | Plastic