LESSMANN®
THE GERMAN BRUSH COMPANY


DATASHEET

Wheel brush with shank



ArtNr. 417C52

Wheel brushes SRBK with 6 x 30 mm shank dia 70 x 10 mm abrasive nylon KK PA6.12 crimped K180 / 1.00 mm trim length 19 mm



Characteristics

Technical data

Overall Height [GH]	46 mm
Filling Height [H]	19 mm
Brush Diameter [D]	70 mm
Grit	K180
Filling Material Diameter	1.00 mm
Filling material	KK PA6.12
Filling Material Shape	Crimped
Net weight	0.001 kg
Art. Description ERP	Wheel brushes SRBK with 6 x 30 mm shank dia 70 x 10 mm abrasive nylon KK PA6.12 crimped K180 / 1.00 mm trim length 19 mm
Filling Width [A]	10 mm
Number of Rows [RZ]	2
RPM max.	15000
Shank Diameter [SD]	6 mm
Tube Diameter [R]	10 mm
Art. Group	Wheel brushes SRBK
Shank Length [LS]	30 mm

Order information

ArtNr	417C52
Packing Unit	10 Stk./pcs./ud.
EAN	4017359789261
Country of origin	D
Commodity code	96035000
PEFC	No

Marketing

Utilizing Industries	Automotive industry | Construction industry | Skilled trades | Metalworking industry
Application	Deburring | Rounding edges | Polishing | Cleaning | Grinding | Structuring
Application Description	The wheel brush is used for deburring, rounding edges, grinding, polishing, structuring and cleaning.
Article Description Marketing	Wheel brush with shank
On Stock as per Catalogue	No
Catalogue Page	81
Product Description short	Wheel brush with a diameter of 70 mm, shank diameter of 6 mm and 180-grit abrasive filaments with ceramic grit

Product Description long	The wheel brush is suitable for deburring, rounding edges, polishing and structuring stainless steel, aluminium and plastic in hand-operated grinders or flexible shafts. Its high-quality abrasive filaments with ceramic grit meet these special requirements. Material removal from the workpiece is abrasive. It can be used for light deburring work. The wheel brush, with its integrated 6 mm shank, is suitable for professional use. The dense filling and perfectly balanced running properties are characteristic of this all-round tool. Of premium "Made in Germany" quality, this product is primarily used in factories and the skilled trades for metalworking, in car repair shops, and in stair, railing and container construction.
Processed Surface	Aluminium | Stainless steel | Plastic | NF metals, hard | Steel

info@lessmann.com | +49 9082 707-0