


Crimped wheel brush with shank



ArtNr. 418362

Wheel brushes SRB with 6 x 30 mm shank dia 80 x 13 mm steel wire stainless ROH crimped 0.30 mm trim length 20 mm



Characteristics

Technical data

Art. Description ERP	Wheel brushes SRB with 6 x 30 mm shank dia 80 x 13 mm steel wire stainless ROH crimped 0.30 mm trim length 20 mm
Overall Height [GH]	50 mm
Filling Material Diameter	0.30 mm
Net weight	0.135 kg
Filling Width [A]	13 mm
Number of Rows [RZ]	2
Shank Diameter [SD]	6 mm
Tube Diameter [R]	12 mm
Shank Length [LS]	30 mm
RPM max.	15000
Brush Diameter [D]	80 mm
Filling Height [H]	20 mm
Filling material	ROH
Filling Material Shape	Crimped
Art. Group	Wheel brushes SRB

Order information

ArtNr	418362
EAN	4017359009529
Commodity code	96035000
Packing Unit	10 Stk./pcs./ud.
PEFC	No
Country of origin	D

Marketing

Utilizing Industries	Automotive industry Construction industry Skilled trades Metalworking industry
Application	Deburring Removing paint Derusting Cleaning Weld seam finishing Structuring
Application Description	The wheel brush is used for cleaning welds, derusting, removing paint, deburring and structuring.
Article Description Marketing	Crimped wheel brush with shank
On Stock as per Catalogue	Yes
Catalogue Page	79
Product Description short	Wheel brush with a diameter of 80 mm, shank diameter of 6 mm and stainless steel wire filling

Product Description long

The wheel brush is used to remove rust, paint, etc., clean welds and for light deburring work. The brush can be mounted in hand-operated grinders and flexible shafts. The stainless steel filling is suitable for stainless steel and aluminium surfaces. The wheel brush, with its integrated 6 mm shank, is suitable for professional use. The dense wire filling and perfectly balanced running properties are characteristic of this product. Of premium "Made in Germany" quality, this product is primarily used in factories and the skilled trades for metalworking, in car repair shops, and in stair, railing and container construction.

Keywords

Automotive industry | Construction industry | Skilled trades | Metalworking industry | Deburring | Removing paint | Derusting | Cleaning | Weld seam finishing | Structuring | Aluminium | Stainless steel | Copper | Steel | Titanium | Zinc | Stainless steel wire | ROF | Wheel brushes | Crimped | Shank

Processed Surface

Aluminium | Stainless steel | Copper | Titanium | Zinc

Description

Wheel brushes with shank

Wheel brushes with shank from LESSMANN are ideal for removing rust, paint and dirt, cleaning welds, and light deburring work. The integrated shank, dense filling and perfectly balanced running properties are characteristic of this all-round tool. Hard-to-reach areas can be processed more easily by mounting brushes of this type in hand-operated grinders or flexible shafts.