


Crimped wheel brush with shank, encapsulated



ArtNr. 451361EP

End brushes SPB with 6 x 25 mm shank dia 12 mm GL 60 mm steel wire stainless ROF crimped 0.30 mm trim length 20 mm single pack



Characteristics

Technical data

Brush Overall Length [GL]	60 mm
Filling Height [H]	20 mm
Brush Diameter [D]	12 mm
Filling Material Diameter	0.30 mm
Filling material	ROF
Filling Material Shape	Crimped
Net weight	0.018 kg
Art. Description ERP	End brushes SPB with 6 x 25 mm shank dia 12 mm GL 60 mm steel wire stainless ROF crimped 0.30 mm trim length 20 mm single pack
RPM max.	20000
Shank Diameter [SD]	6 mm
Housing Diameter [DH]	10 mm
Art. Group	End brushes SPB
Shank Length [LS]	25 mm

Order information

ArtNr	451361EP
Packing Unit	1 Stk./pcs./ud.
EAN	4017359833780
Secondary Packing Unit	10 Stk./pcs./ud.
Country of origin	D
Commodity code	96035000
PEFC	No

Marketing

Utilizing Industries	Construction industry Skilled trades Metalworking industry Automotive industry
Application	Derusting Removing paint Cleaning Weld seam finishing Deburring Removing slag Removing scale
Application Description	The wheel brush is used for derusting, removing paint and cleaning welds.
Article Description Marketing	Crimped wheel brush with shank, encapsulated
On Stock as per Catalogue	Yes
Version	Encapsulated
Catalogue Page	143
Product Description short	Wheel brush with a diameter of 60 mm, shank diameter of 6 mm and encapsulated steel wire filling

Product Description long

The wheel brush is used to remove rust, paint, etc. and to clean welds. The brush can be mounted in hand-operated grinders and flexible shafts. The steel filling is suitable for steel surfaces. The aggressiveness is: hard. With its permanently mounted 6 mm shank, it is suitable for professional use. The dense wire filling and perfectly balanced running properties are characteristic of this all-round tool. In this encapsulated brush, the steel wire filling is embedded in a tough polymer compound. The filling width remains constant during use as a result, and encapsulation prevents premature breakage of individual wires. Of premium "Made in Germany" quality, this product is primarily used in factories and the skilled trades for metalworking, in car repair shops, and in stair, railing and container construction.

Processed Surface

Titanium | Cast iron | Aluminium |
Stainless steel | Copper | Zinc