LESSMANN®
THE GERMAN BRUSH COMPANY

DATASHEET

Crimped end brush with shank

ArtNr. 451361

End brushes SPB with 6 x 25 mm shank dia 12 mm GL 60 mm steel wire stainless ROF crimped 0.30 mm trim length 20 mm



Characteristics

Technical data

Art. Description ERP	End brushes SPB with 6 x 25 mm shank dia 12 mm GL 60 mm steel wire stainless ROF crimped 0.30 mm trim length 20 mm
Brush Overall Length [GL]	60 mm
Filling Height [H]	20 mm
Filling Material Diameter	0.30 mm
Net weight	0.017 kg
Shank Diameter [SD]	6 mm
Housing Diameter [DH]	10 mm
Shank Length [LS]	25 mm
RPM max.	20000
Brush Diameter [D]	12 mm
Filling material	ROF
Filling Material Shape	Crimped
Art. Group	End brushes SPB

Order information

ArtNr	451361
EAN	4017359006801
Commodity code	96035000
Packing Unit	10 Stk./pcs./ud.
PEFC	No
Country of origin	D

Marketing

Utilizing Industries	Automotive industry | Construction industry | Skilled trades | Metalworking industry
Application	Deburring | Removing paint | Removing slag | Removing scale | Cleaning
Application Description	The end brush is used for cleaning, removing paint, slag and scale, and deburring.
Article Description Marketing	Crimped end brush with shank
On Stock as per Catalogue	Yes
Catalogue Page	87
Product Description short	End brush with a diameter of 12 mm, shank diameter of 6 mm and stainless steel wire filling

Product Description long	The end brush can be mounted in hand-operated grinders or flexible shafts. It is used to work on hard-to-reach areas, and to clean corners, recessed spots and bore holes. It also is used to clean moulds/castings and to remove residual paint and rubber. The stainless steel filling is suitable for stainless steel and aluminium surfaces. The aggressiveness is: moderate. The brush, with its permanently mounted 6 mm shank, is suitable for professional use and for high-speed rotating tools. Of premium "Made in Germany" quality, this product is primarily used in factories and the skilled trades for metalworking, in car repair shops, and in stair, railing and container construction.
Keywords	Automotive industry | Construction industry | Skilled trades | Metalworking industry | Deburring | Removing paint | Removing slag | Removing scale | Cleaning | Aluminium | Stainless steel | Cast iron | Copper | Steel | Titanium | Zinc | Stainless steel wire | ROF | End brush | Crimped | Shank
Processed Surface	Aluminium | Stainless steel | Cast iron | Copper | Titanium | Zinc

Description

End brushes with shank
End brushes with shank from LESSMANN are used to best advantage to clean and deburr very hard-to-reach areas, remove residual paint and rubber, and to clean moulds and castings. They are also effective for working on corners, rounded contours and recessed areas inside bore holes. The brushes, with their permanently mounted shank, are suitable for professional use and for high-speed rotating tools.