


Knotted end brush with shank



ArtNr. 451458

Knot end brush SZP with 6 x 20 mm shank dia 10 mm 1 row x 1 Z fully knotted right steel wire stainless RO4 1.4401 straight 0.25 mm trim length 25 mm



Characteristics

Technical data

Filling Material Shape	Straight
Knot Direction	right
Art. Description ERP	Knot end brush SZP with 6 x 20 mm shank dia 10 mm 1 row x 1 Z fully knotted right steel wire stainless RO4 1.4401 straight 0.25 mm trim length 25 mm
Filling Height [H]	25 mm
Filling Material Diameter	0.25 mm
Net weight	0.017 kg
Number of Rows [RZ]	1
Shank Diameter [SD]	6 mm
Housing Diameter [DH]	10 mm
Body Length [KL]	40 mm
RPM max.	4500
Brush Diameter [D]	6 mm
Brush Overall Length [GL]	65 mm
Filling Width [A]	6 mm
Knots per Row [Z]	1
Shank Length [LS]	20 mm
Filling material	RO4 1.4401
Knot End [ZF]	Fully knotted
Art. Group	Knot end brushes SZP

Order information

ArtNr	451458
EAN	4017359208915
Commodity code	96035000
Packing Unit	10 Stk./pcs./ud.
PEFC	No
Country of origin	D

Marketing

Utilizing Industries	Automotive industry Construction industry Skilled trades Metalworking industry Shipbuilding
Application	Deburring Removing paint Removing slag Removing scale Cleaning
Application Description	The end brush is used for cleaning, removing paint, slag and scale, and deburring.
Article Description Marketing	Knotted end brush with shank
On Stock as per Catalogue	Yes
Catalogue Page	89
Product Description short	Knot end brush with 1 knot, a diameter of 10 mm, shank diameter of 6 mm and stainless steel wire filling

Product Description long

The knot end brush can be mounted in hand-operated grinders or flexible shafts. It is used to work on hard-to-reach areas, and to clean corners, recessed spots and bore holes. It also is used to clean moulds /castings and to remove residual paint and rubber. The stainless steel filling is suitable for stainless steel and aluminium surfaces. The aggressiveness is soft with an aggressive effect in use. The brush, with its permanently mounted 6 mm shank, is suitable for professional use and for a maximum speed of 4500 RPM. Of premium "Made in Germany" quality, this product is primarily used in factories and the skilled trades for metalworking, in car repair shops, and in stair, railing and container construction.

Keywords

Automotive industry | Construction industry | Skilled trades | Metalworking industry | Shipbuilding | Deburring | Removing paint | Removing slag | Removing scale | Cleaning | Aluminium | Stainless steel | Cast iron | Copper | Steel | Titanium | Zinc | Fully knotted | Stainless steel wire | RO4 | End brush | Knotted | Shank

Processed Surface

Aluminium | Stainless steel | Cast iron | Copper | Titanium | Zinc

Description

Knotted end brushes with shank

Knotted end brushes with shank from LESSMANN are used to best advantage to clean and deburr very hard-to-reach areas, remove residual paint and rubber, and to clean moulds and castings. The brushes, with their permanently mounted shank, are suitable for professional use and for high-speed rotating tools. The brush opens more or less wide, depending on the RPM; the aggressiveness is: hard.

Knotted end brushes with shank, 1 knot

End brushes with 1 knot are suitable for precision work; the aggressiveness is: hard.