


Knotted end brush with shank



ArtNr. 453238

Knot end brush SZP with 6 x 18 mm shank dia 19 mm 1 row x 6 Z rose bud right steel wire STH straight 0.15 mm trim length 28 mm



Characteristics

Technical data

Filling Material Shape	Straight
Knot Direction	right
Art. Description ERP	Knot end brush SZP with 6 x 18 mm shank dia 19 mm 1 row x 6 Z rose bud right steel wire STH straight 0.15 mm trim length 28 mm
Filling Height [H]	28 mm
Filling Material Diameter	0.15 mm
Net weight	0.048 kg
Number of Rows [RZ]	1
Housing Diameter [DH]	19 mm
Body Length [KL]	43 mm
Brush Diameter [D]	19 mm
Brush Overall Length [GL]	72 mm
Filling Width [A]	8 mm
Knots per Row [Z]	6
RPM max.	20000
Shank Diameter [SD]	6 mm
Shank Length [LS]	18 mm
Filling material	STH
Knot End [ZF]	Rose bud
Art. Group	Knot end brushes SZP

Order information

ArtNr	453238
EAN	4017359214718
Commodity code	96035000
Packing Unit	10 Stk./pcs./ud.
PEFC	No
Country of origin	D

Marketing

Utilizing Industries	Automotive industry Construction industry Skilled trades Metalworking industry Shipbuilding
Application	Deburring Removing paint Removing slag Removing scale Cleaning
Application Description	The end brush is used for cleaning, removing paint, slag and scale, and deburring.
Article Description Marketing	Knotted end brush with shank
On Stock as per Catalogue	No
Catalogue Page	89
Product Description short	Knot end brush with 6 knots, a diameter of 19 mm, shank diameter of 6 mm and steel wire filling

Product Description long

The knot end brush can be mounted in hand-operated grinders or flexible shafts. It is used to work on hard-to-reach areas, and to clean corners, recessed spots and bore holes. It also is used to clean moulds /castings and to remove residual paint and rubber. The steel filling is suitable for steel surfaces. The brush, with its permanently mounted 6 mm shank, is suitable for professional use and for high-speed rotating tools. The brush opens more or less wide, depending on the RPM. Of premium "Made in Germany" quality, this product is primarily used in factories and the skilled trades for metalworking, in car repair shops, and in stair, railing and container construction.

Keywords

Automotive industry | Construction industry | Skilled trades | Metalworking industry | Shipbuilding | Deburring | Removing paint | Removing slag | Removing scale | Cleaning | Cast iron | Steel | Rose bud | Steel wire | High-tensile wire | STH | End brush | Knotted | Shank

Processed Surface

Cast iron | Steel

Description

Knotted end brushes with shank

Knotted end brushes with shank from LESSMANN are used to best advantage to clean and deburr very hard-to-reach areas, remove residual paint and rubber, and to clean moulds and castings. The brushes, with their permanently mounted shank, are suitable for professional use and for high-speed rotating tools. The brush opens more or less wide, depending on the RPM; the aggressiveness is: hard.