LESSMANN®
THE GERMAN BRUSH COMPANY


DATASHEET

Cup brush with shank



ArtNr. 454278EP

Knot end brush SZP with 6 x 16 mm shank dia 22.5 mm 1 row x 8 Z rose bud right steel wire STH straight 0.35 mm trim length 28 mm single pack



Characteristics

Technical data

Filling Material Shape	Straight
Knot Direction	right
Brush Overall Length [GL]	72 mm
Filling Height [H]	28 mm
Brush Diameter [D]	22 mm
Filling Material Diameter	0.35 mm
Filling material	STH
Net weight	0.074 kg
Art. Description ERP	Knot end brush SZP with 6 x 16 mm shank dia 22.5 mm 1 row x 8 Z rose bud right steel wire STH straight 0.35 mm trim length 28 mm single pack
Filling Width [A]	8 mm
Knot End [ZF]	Rose bud
Number of Rows [RZ]	1
Knots per Row [Z]	8
RPM max.	20000
Shank Diameter [SD]	6 mm
Housing Diameter [DH]	22.5 mm
Art. Group	Knot end brushes SZP
Body Length [KL]	43 mm
Shank Length [LS]	16 mm

Order information

ArtNr	454278EP
Packing Unit	1 Stk./pcs./ud.
EAN	4017359833957
Seconday Packing Unit	10 Stk./pcs./ud.
Country of origin	D
Commodity code	96035000
PEFC	No

Marketing

Utilizing Industries	Construction industry | Skilled trades | Metalworking industry | Automotive industry | Shipbuilding
Application	Derusting | Removing paint | Removing scale | Polishing | Cleaning | Deburring | Removing slag
Application Description	The knot cup brush is used for cleaning, derusting, polishing, removing paint and slag, and deburring.
Article Description Marketing	Cup brush with shank
On Stock as per Catalogue	Yes
Catalogue Page	143
Product Description short	Cup shank brush, with a diameter of 50 mm, shank diameter of 6 mm and steel wire filling

info@lessmann.com | +49 9082 707-0

Product Description long	The cup shank brush is mounted in hand-operated grinders and flexible shafts. It is used for derusting and polishing, removing paint and dirt, and light deburring work. The steel filling is well suited to large steel surfaces. The aggressiveness is: moderate. The brush, with its permanently mounted 6 mm shank, is suitable for professional use. The dense wire filling and perfectly balanced running properties are characteristic of this product. Of premium "Made in Germany" quality, this product is primarily used in factories and the skilled trades for metalworking, in car repair shops, and in stair, railing and container construction.
Processed Surface	Titanium | Cast iron | Steel