LESSMANN®
THE GERMAN BRUSH COMPANY


DATASHEET

Crimped end brush with shank



ArtNr. 458161EP

End brushes SPB with 6 x 25 mm shank dia 12 mm GL 120 mm steel wire STA crimped 0.30 mm trim length 20 mm single pack



Characteristics

Technical data

Brush Overall Length [GL]	120 mm
Filling Height [H]	20 mm
Brush Diameter [D]	12 mm
Filling Material Diameter	0.30 mm
Filling material	STA
Filling Material Shape	Crimped
Net weight	0.061 kg
Art. Description ERP	End brushes SPB with 6 x 25 mm shank dia 12 mm GL 120 mm steel wire STA crimped 0.30 mm trim length 20 mm single pack
RPM max.	15000
Shank Diameter [SD]	6 mm
Housing Diameter [DH]	10 mm
Art. Group	End brushes SPB
Shank Length [LS]	25 mm

Order information

ArtNr	458161EP
Packing Unit	1 Stk./pcs./ud.
EAN	4017359833827
Seconday Packing Unit	10 Stk./pcs./ud.
Country of origin	D
Commodity code	96035000
PEFC	No

Marketing

Utilizing Industries	Automotive industry | Construction industry | Skilled trades | Metalworking industry
Application	Deburring | Removing paint | Removing slag | Removing scale | Cleaning
Application Description	The end brush is used for cleaning, removing paint, slag and scale, and deburring.
Article Description Marketing	Crimped end brush with shank
On Stock as per Catalogue	Yes
Catalogue Page	143
Product Description short	End brush with a diameter of 17 mm, shank diameter of 6 mm and steel wire filling

info@lessmann.com | +49 9082 707-0

Product Description long	The end brush can be mounted in hand-operated grinders or flexible shafts. It is used to work on hard-to-reach areas, and to clean corners, recessed spots and bore holes. It also is used to clean moulds/castings and to remove residual paint and rubber. The steel filling is suitable for steel surfaces. The aggressiveness is: moderate. The brush, with its permanently mounted 6 mm shank, is suitable for professional use and for high-speed rotating tools. Of premium "Made in Germany" quality, this product is primarily used in factories and the skilled trades for metalworking, in car repair shops, and in stair, railing and container construction.
Processed Surface	Wood | Steel | Cast iron