


Knotted wheel brush



ArtNr. 471817

Knot wheel brushes ZR dia 100 x 12 mm 1 row x 18 Z rose bud left steel wire stainless ROH straight 0.50 mm thread M14 trim length 21 mm



Characteristics

Technical data

Filling Material Shape	Straight
Art. Description ERP	Knot wheel brushes ZR dia 100 x 12 mm 1 row x 18 Z rose bud left steel wire stainless ROH straight 0.50 mm thread M14 trim length 21 mm
Filling Material Diameter	0.50 mm
Net weight	0.27 kg
Filling Width [A]	12 mm
Number of Rows [RZ]	1
RPM max.	12500
Brush Diameter [D]	100 mm
Filling Height [H]	21 mm
Knots per Row [Z]	18
Filling material	ROH
Thread Interior Diameter [GI]	M14
Knot End [ZF]	Rose bud
Knot Direction	left
Art. Group	Knot wheel brushes ZR

Order information

ArtNr	471817
EAN	4017359053744
Secondary Packing Unit	10 Stk./pcs./ud.
Commodity code	96035000
Packing Unit	1 Stk./pcs./ud.
PEFC	No
Country of origin	D

Marketing

Utilizing Industries	Automotive industry Construction industry Skilled trades Metalworking industry Pipeline construction
Application	Deburring Removing paint Derusting Removing slag Removing scale Cleaning Weld seam finishing
Application Description	The knot wheel brush is used for deburring, processing welds, cleaning, descaling and removing rust, paint and slag.
Article Description Marketing	Knotted wheel brush
On Stock as per Catalogue	No
Version	with thread
Catalogue Page	19
Product Description short	Knot wheel brush with 18 knots, a diameter of 100 mm, M14 thread and stainless steel wire filling

Product Description long	The knot wheel brush is suitable for use with hand-operated angle grinders to process weld seams or to remove scale, rust, paint, slag and residual concrete. The brush with stainless steel wire is well suited to large stainless steel and aluminium surfaces. The knotted wheel brush is suitable for professional use. The left-twisted knots of the knotted brush increase its durability. Of premium "Made in Germany" quality, this product is primarily used in factories and the skilled trades for metalworking, in car repair shops, and in stair, railing and container construction.
Keywords	Automotive industry Construction industry Skilled trades Metalworking industry Pipeline construction Deburring Removing paint Derusting Removing slag Removing scale Cleaning Weld seam finishing Aluminium Stainless steel Copper Steel Titanium Zinc Rose bud Stainless steel wire High-tensile wire ROH Wheel brushes Knotted Thread
Processed Surface	Aluminium Stainless steel Copper Titanium Zinc

Description

Knotted wheel brushes

Knotted wheel brushes from LESSMANN are used in angle grinders and stationary machines for weld preparation and finishing (fillet and butt welds). The aggressive brushes remove scale, rust, paint, slag and rubber residue, and deburr edges. The knots are left-twisted to promote a longer service life: Left-twisted wire knots prevent the bundles from opening prematurely when the brush is used at an angle.