LESSMANN®
THE GERMAN BRUSH COMPANY


DATASHEET

Knotted wheel brush



ArtNr. 47281X

Knot wheel brushes ZR dia 115 x 14 mm 1 row x 20 Z rose bud left steel wire stainless ROH straight 0.50 mm bore X-LOCK mm trim length 23.5 mm



Characteristics

Technical data

Filling Material Shape	Straight
Art. Description ERP	Knot wheel brushes ZR dia 115 x 14 mm 1 row x 20 Z rose bud left steel wire stainless ROH straight 0.50 mm bore X-LOCK mm trim length 23.5 mm
Filling Height [H]	23.5 mm
Filling Material Diameter	0.50 mm
Bore Diameter [DB]	X-LOCK mm
Net weight	0.302 kg
Filling Width [A]	14 mm
RPM max.	12500
Brush Diameter [D]	115 mm
Number of Rows [RZ]	1
Knots per Row [Z]	20
Filling material	ROH
Knot End [ZF]	Rose bud
Knot Direction	left
Art. Group	Knot wheel brushes ZR

Order information

ArtNr	47281X
EAN	4017359588154
Seconday Packing Unit	0 Stk./pcs./ud.
Commodity code	96035000
Packing Unit	1 Stk./pcs./ud.
PEFC	No
Country of origin	D

Marketing

Utilizing Industries	Automotive industry | Construction industry | Skilled trades | Metalworking industry | Pipeline construction
Application	Deburring | Removing paint | Derusting | Removing slag | Removing scale | Cleaning | Weld seam finishing
Application Description	The knot wheel brush is used for deburring, processing welds, cleaning, descaling and removing rust, paint and slag.
Article Description Marketing	Knotted wheel brush
On Stock as per Catalogue	Yes
Version	X-Lock
Catalogue Page	71
Product Description short	Knot wheel brush with 20 knots, a diameter of 115 mm, X-Lock and stainless steel wire filling

info@lessmann.com | +49 9082 707-0

Product Description long	The knot wheel brush is suitable for use with hand-operated angle grinders from Bosch to process weld seams or to remove scale, rust, paint, slag and residual concrete. The brush with stainless steel wire is well suited to large stainless steel and aluminium surfaces. The knotted wheel brush is suitable for professional use. The left-twisted knots of the knotted brush increase its durability. The aggressiveness is: hard. Of premium "Made in Germany" quality, this product is primarily used in factories and the skilled trades for metalworking, in car repair shops, and in stair, railing and container construction.
Keywords	Automotive industry | Construction industry | Skilled trades | Metalworking industry | Pipeline construction | Deburring | Removing paint | Derusting | Removing slag | Cleaning | Weld seam finishing | Aluminium | Stainless steel | Copper | Steel | Titanium | Zinc | Rose bud | Stainless steel wire | ROH | High-tensile wire | Wheel brushes | Knotted | X-LOCK
Processed Surface	Aluminium | Stainless steel | Copper | Titanium | Zinc

Description

Knotted wheel brushes
Knotted wheel brushes from LESSMANN are used in angle grinders and stationary machines for weld preparation and finishing (fillet and butt welds). The aggressive brushes remove scale, rust, paint, slag and rubber residue, and deburr edges. The knots are left-twisted to promote a longer service life: Left-twisted wire knots prevent the bundles from opening prematurely when the brush is used at an angle.