


Knotted cup brush



ArtNr. 480217

Knot cup brushes ZT dia 80 -85 x 14 mm 1 row x 18 Z rose bud right steel wire STH straight 0.50 mm thread M14 trim length 33 mm



Characteristics

Technical data

Filling Material Shape	Straight
Knot Direction	right
Art. Description ERP	Knot cup brushes ZT dia 80 -85 x 14 mm 1 row x 18 Z rose bud right steel wire STH straight 0.50 mm thread M14 trim length 33 mm
Filling Height [H]	33 mm
Filling Material Diameter	0.50 mm
Net weight	0.3202 kg
RPM max.	12500
Brush Diameter [D]	80 -85 mm
Number of Rows [RZ]	1
Overall Height [GH]	63 mm
Filling Width [A]	14 mm
Knots per Row [Z]	18
Filling material	STH
Thread Interior Diameter [GI]	M14
Knot End [ZF]	Rose bud
Art. Group	Knot cup brushes ZT

Order information

ArtNr	480217
EAN	4017359299746
Secondary Packing Unit	0 Stk./pcs./ud.
Commodity code	96035000
Packing Unit	25 Stk./pcs./ud.
PEFC	No
Country of origin	D

Marketing

Utilizing Industries	Automotive industry Construction industry Skilled trades Metalworking industry Shipbuilding
Application	Removing paint Derusting Removing slag Removing scale Cleaning Weld seam finishing
Application Description	The knot cup brush is used for processing welds, cleaning, and removing scale, rust, paint and slag.
Article Description Marketing	Knotted cup brush
On Stock as per Catalogue	No
Version	extra-long filling
Catalogue Page	59
Product Description short	Knot cup brush with 18 knots, a diameter of 80 mm, M14 thread and steel wire filling

Product Description long	The knot cup brush is suitable for use with hand-operated angle grinders to process weld seams or to remove scale, rust, paint, slag and residual concrete. The brush with steel wire is well suited to large steel surfaces. The knotted cup brush is suitable for professional use. This cup brush ensures smooth operation with its perfectly balanced running properties. Of premium "Made in Germany" quality, this product is primarily used in factories and the skilled trades for metalworking, in car repair shops, and in stair, railing and container construction.
Keywords	Automotive industry Construction industry Skilled trades Metalworking industry Shipbuilding Removing paint Derusting Removing slag Removing scale Cleaning Weld seam finishing Steel Rose bud Steel wire High-tensile wire STH Cup brush Knotted Thread
Processed Surface	Steel

Description

Knotted cup brushes

Knotted cup brushes from LESSMANN are ideal for heavy duty use, e.g. to prepare metal surfaces for painting or remove slag, rust, scale and residual concrete. The knots are left-twisted to promote a longer service life: Left-twisted wire knots prevent the bundles from opening prematurely when the brush is used at an angle.

Knotted cup brushes with extra-long filling

These brushes are ideal for the flexible cleaning and derusting of large surface areas, e.g. in shipyards. They usually are used in hand-operated angle grinders. This additionally facilitates work on hard-to-reach corners.