


Knotted cup brush



ArtNr. 482817WZ

Knot cup brushes ZT dia 65 x 12 mm 1 row x 18 Z rose bud right / left steel wire stainless ROH straight 0.50 mm thread M14 trim length 20 mm



Characteristics

Technical data

Filling Material Shape	Straight
Art. Description ERP	Knot cup brushes ZT dia 65 x 12 mm 1 row x 18 Z rose bud right / left steel wire stainless ROH straight 0.50 mm thread M14 trim length 20 mm
Filling Height [H]	20 mm
Filling Material Diameter	0.50 mm
Net weight	0.28 kg
RPM max.	12500
Brush Diameter [D]	65 mm
Filling Width [A]	12 mm
Number of Rows [RZ]	1
Overall Height [GH]	53 mm
Knots per Row [Z]	18
Filling material	ROH
Thread Interior Diameter [GI]	M14
Knot End [ZF]	Rose bud
Knot Direction	right/left
Art. Group	Knot cup brushes ZT

Order information

ArtNr	482817WZ
EAN	4017359380130
Secondary Packing Unit	10 Stk./pcs./ud.
Commodity code	96035000
Packing Unit	1 Stk./pcs./ud.
PEFC	No
Country of origin	D

Marketing

Utilizing Industries	Automotive industry Construction industry Skilled trades Metalworking industry Shipbuilding
Application	Removing paint Derusting Removing slag Removing scale Cleaning Weld seam finishing
Application Description	The knot cup brush is used for processing welds, cleaning, and removing scale, rust, paint and slag.
Article Description Marketing	Knotted cup brush
On Stock as per Catalogue	Yes
Version	left-right knotted
Catalogue Page	61
Product Description short	Knot cup brush with 18 knots, a diameter of 65 mm, M14 thread and filling of right-/left-twisted stainless steel wire knots

Product Description long	The knot cup brush is suitable for use with hand-operated angle grinders to process weld seams or to remove scale, rust, paint, slag and residual concrete. The brush with stainless steel wire is well suited to large stainless steel and aluminium surfaces. The knotted cup brush is suitable for professional use and ensures smooth operation with its perfectly balanced running properties. The brush with left-right knotting is generally more aggressive and ideal for work around corners and edges. Of premium "Made in Germany" quality, this product is primarily used in factories and the skilled trades for metalworking, in car repair shops, and in stair, railing and container construction.
Keywords	Automotive industry Construction industry Skilled trades Metalworking industry Shipbuilding Removing paint Derusting Removing slag Removing scale Cleaning Weld seam finishing Aluminium Stainless steel Copper Steel Titanium Zinc Rose bud Stainless steel wire High-tensile wire ROH Cup brush Knotted Thread
Processed Surface	Aluminium Stainless steel Copper Titanium Zinc

Description

Knotted cup brushes

Knotted cup brushes from LESSMANN are ideal for heavy duty use, e.g. to prepare metal surfaces for painting or remove slag, rust, scale and residual concrete. The knots are left-twisted to promote a longer service life: Left-twisted wire knots prevent the bundles from opening prematurely when the brush is used at an angle.

Brushes, left-right knotted

Brushes with left-right knotting generally are more aggressive, meaning they are often used for very heavy-duty brush work. Because the knots unravel less easily, they are ideal for working corners and edges.