


Knotted cup brush



ArtNr. 48321X

Knot cup brushes ZT dia 85 x 12 mm 1 row x 20 Z rose bud right steel wire STH straight 0.50 mm bore X-LOCK mm trim length 20 mm



Characteristics

Technical data

Filling Material Shape	Straight
Knot Direction	right
Art. Description ERP	Knot cup brushes ZT dia 85 x 12 mm 1 row x 20 Z rose bud right steel wire STH straight 0.50 mm bore X-LOCK mm trim length 20 mm
Filling Height [H]	20 mm
Filling Material Diameter	0.50 mm
Bore Diameter [DB]	X-LOCK mm
Net weight	0.332 kg
Number of Rows [RZ]	1
RPM max.	11500
Overall Height [GH]	44 mm
Brush Diameter [D]	85 mm
Filling Width [A]	12 mm
Knots per Row [Z]	20
Filling material	STH
Knot End [ZF]	Rose bud
Art. Group	Knot cup brushes ZT

Order information

ArtNr	48321X
EAN	4017359620106
Seconday Packing Unit	0 Stk./pcs./ud.
Commodity code	96035000
Packing Unit	1 Stk./pcs./ud.
PEFC	No
Country of origin	D

Marketing

Utilizing Industries	Automotive industry Construction industry Skilled trades Metalworking industry Shipbuilding
Application	Removing paint Derusting Removing slag Removing scale Cleaning Weld seam finishing
Application Description	The knot cup brush is used for processing welds, cleaning, and removing scale, rust, paint and slag.
Article Description Marketing	Knotted cup brush
On Stock as per Catalogue	Yes
Version	X-Lock
Catalogue Page	71
Product Description short	Knot cup brush with 20 knots, a diameter of 85 mm, X-Lock and steel wire filling

Product Description long	The knot cup brush is suitable for use with hand-operated angle grinders from Bosch to process weld seams or to remove scale, rust, paint, slag and residual concrete. The brush with steel wire is well suited to large steel surfaces. The aggressiveness is: hard. The knotted cup brush is suitable for professional use. This cup brush ensures smooth operation with its perfectly balanced running properties. Of premium "Made in Germany" quality, this product is primarily used in factories and the skilled trades for metalworking, in car repair shops, and in stair, railing and container construction.
Keywords	Automotive industry Construction industry Skilled trades Metalworking industry Shipbuilding Removing paint Derusting Removing slag Removing scale Cleaning Weld seam finishing Steel Rose bud Steel wire High-tensile wire STH Cup brush Knotted X-LOCK
Processed Surface	Steel

Description

Knotted cup brushes

Knotted cup brushes from LESSMANN are ideal for heavy duty use, e.g. to prepare metal surfaces for painting or remove slag, rust, scale and residual concrete. The knots are left-twisted to promote a longer service life: Left-twisted wire knots prevent the bundles from opening prematurely when the brush is used at an angle.