LESSMANN®
THE GERMAN BRUSH COMPANY


DATASHEET

Knotted cup brush



ArtNr. 486148

Knot cup brushes ZT dia 100 x 18 mm 2 row x 26/20 Z fully knotted right steel wire STH straight 0.35 mm thread 5/8" -11 trim length 25 mm



Characteristics

Technical data

Filling Material Shape	Straight
Knot Direction	right
Art. Description ERP	Knot cup brushes ZT dia 100 x 18 mm 2 row x 26/20 Z fully knotted right steel wire STH straight 0.35 mm thread 5/8"-11 trim length 25 mm
Filling Height [H]	25 mm
Filling Material Diameter	0.35 mm
Net weight	0.0001 kg
Brush Diameter [D]	100 mm
Number of Rows [RZ]	2
Overall Height [GH]	70 mm
Filling Width [A]	18 mm
RPM max.	9000
Knots per Row [Z]	26/20
Filling material	STH
Thread Interior Diameter [GI]	5/8"-11
Knot End [ZF]	Fully knotted
Art. Group	Knot cup brushes ZT

Order information

ArtNr	486148
EAN	4017359299760
Commodity code	96035000
Packing Unit	1 Stk./pcs./ud.
PEFC	No
Country of origin	D

Marketing

Utilizing Industries	Automotive industry | Construction industry | Skilled trades | Metalworking industry | Shipbuilding
Application	Removing paint | Derusting | Removing slag | Removing scale | Cleaning | Weld seam finishing
Application Description	The knot cup brush is used for processing welds, cleaning, and removing scale, rust, paint and slag.
Article Description Marketing	Knotted cup brush
On Stock as per Catalogue	No
Catalogue Page	59
Product Description short	Knot cup brush with 26+20 knots, a diameter of 100 mm, 5/8" thread and steel wire filling

Product Description long	The knot cup brush is suitable for use with hand-operated angle grinders to process weld seams or to remove scale, rust, paint, slag and residual concrete. The brush with steel wire is well suited to large steel surfaces. The knotted cup brush is suitable for professional use. This cup brush ensures smooth operation with its perfectly balanced running properties. Of premium "Made in Germany" quality, this product is primarily used in factories and the skilled trades for metalworking, in car repair shops, and in stair, railing and container construction.
Keywords	Automotive industry | Construction industry | Skilled trades | Metalworking industry | Shipbuilding | Removing paint | Derusting | Removing slag | Removing scale | Cleaning | Weld seam finishing | Steel | Fully knotted | Steel wire | High-tensile wire | STH | Cup brush | Knotted | Thread
Processed Surface	Steel

Description

Knotted cup brushes
Knotted cup brushes from LESSMANN are ideal for heavy duty use, e.g. to prepare metal surfaces for painting or remove slag, rust, scale and residual concrete. The knots are left-twisted to promote a longer service life: Left-twisted wire knots prevent the bundles from opening prematurely when the brush is used at an angle.

Knotted brushes, multiple-row
These brushes have a denser filling with several rows, meaning they are more effective than brushes with a single row.