


Knotted cup brush with bridle



ArtNr. 486218

Knot cup brushes ZT with bridle dia 100 x 14 mm 1 row x 26 Z rose bud right steel wire STH straight 0.50 mm thread 5/8"-11 trim length 23 mm



Characteristics

Technical data

Filling Material Shape	Straight
Knot Direction	right
Art. Description ERP	Knot cup brushes ZT with bridle dia 100 x 14 mm 1 row x 26 Z rose bud right steel wire STH straight 0.50 mm thread 5/8"-11 trim length 23 mm
Filling Height [H]	23 mm
Filling Material Diameter	0.50 mm
Net weight	0.93 kg
Additional Filling Height [H1]	12 mm
RPM max.	9000
Brush Diameter [D]	100 mm
Number of Rows [RZ]	1
Overall Height [GH]	74 mm
Filling Width [A]	14 mm
Knots per Row [Z]	26
Filling material	STH
Thread Interior Diameter [GI]	5/8"-11
Knot End [ZF]	Rose bud
Art. Group	Knot cup brushes ZT

Order information

ArtNr	486218
EAN	4017359018187
Seconday Packing Unit	10 Stk./pcs./ud.
Commodity code	96035000
Packing Unit	1 Stk./pcs./ud.
PEFC	No
Country of origin	D

Marketing

Utilizing Industries	Automotive industry Construction industry Skilled trades Metalworking industry Shipbuilding
Application	Removing paint Derusting Removing slag Removing scale Cleaning Weld seam finishing
Application Description	The knot cup brush is used for processing welds, cleaning, and removing scale, rust, paint and slag.
Article Description Marketing	Knotted cup brush with bridle
On Stock as per Catalogue	Yes
Version	with bridle
Catalogue Page	60
Product Description short	Knot cup brush with bridle, 26 knots, a diameter of 100 mm, 5/8" thread and steel wire filling

Product Description long	The knot cup brush is suitable for use with hand-operated angle grinders to process weld seams or to remove scale, rust, paint, slag and residual concrete. The brush with steel wire is well suited to large steel surfaces. The knotted cup brush is suitable for professional use. This cup brush ensures smooth operation with its perfectly balanced running properties. Of premium "Made in Germany" quality, this product is primarily used in factories and the skilled trades for metalworking, in car repair shops, and in stair, railing and container construction.
Keywords	Automotive industry Construction industry Skilled trades Metalworking industry Shipbuilding Removing paint Derusting Removing slag Removing scale Cleaning Weld seam finishing Steel Rose bud Steel wire High-tensile wire STH Cup brush Knotted Thread
Processed Surface	Steel

Description

Knotted cup brushes

Knotted cup brushes from LESSMANN are ideal for heavy duty use, e.g. to prepare metal surfaces for painting or remove slag, rust, scale and residual concrete. The knots are left-twisted to promote a longer service life: Left-twisted wire knots prevent the bundles from opening prematurely when the brush is used at an angle.

Brushes with bridle

The bridle stabilises the brush and can easily be removed once the exposed wire filling has worn down. As a result, additional filling material is available for further brush use.