LESSMANN®
THE GERMAN BRUSH COMPANY


DATASHEET

Sleeve brush IBD



ArtNr. 549105

Sleeve internal brushes IBD pinched off tip 170 x 100 mm conical across dia 32/42 mm steel wire STA straight 0.40 mm core wire black 4x 4.0 mm = shank 10.6 mm



Characteristics

Technical data

Filling Material Shape	Straight
Brush Overall Length [GL]	170 mm
Filling Material Diameter	0.40 mm
Net weight	0.129 kg
Art. Description ERP	Sleeve internal brushes IBD pinched off tip 170 x 100 mm conical across dia 32/42 mm steel wire STA straight 0.40 mm core wire black 4x 4.0 mm = shank 10.6 mm
Filling Length [BL]	100 mm
Twisted Wire Diameter	4.0 mm
RPM max.	1000
Brush Diameter [D]	32/42 mm
Brush Tip	Clipped
Shank Twisted Wire Diameter [SD]	10.6 mm
Filling material	STA
Brush Shape	Conical, crosswise
Twisted Wire Material	Black 4x
Tip Shape	Clipped off tip
Art. Group	Interior brushes

Order information

ArtNr	549105
EAN	4017359031964
Commodity code	96039099
Packing Unit	5 Stk./pcs./ud.
PEFC	No
Country of origin	D

Marketing

Utilizing Industries	Plastics industry | Metalworking industry
Application	Cleaning | Removing paint | Derusting
Application Description	The sleeve brush is used for cleaning, derusting and stripping paint.
Article Description Marketing	Sleeve brush IBD
On Stock as per Catalogue	Yes
Version	with double spiral
Single/Double Spiral	Double spiral
Catalogue Page	127
Product Description short	Sleeve brush IBD with a total length of 170 mm, diameter of 32 /42 mm and conically trimmed steel wire filling configured crosswise

Product Description long	The sleeve brush is used for the manual or machine removal of rust, dirt and paint. The conically trimmed steel wire filling, configured crosswise, is suitable for steel surfaces. For use on interior areas, the diameter should be selected to match the workpiece. Of premium "Made in Germany" quality, this product is frequently used in container construction and in the metalworking and plastics industries.
Keywords	Plastics industry | Metalworking industry | Removing paint | Derusting | Cleaning | Steel | Steel wire | STA | Sleeve brush
Processed Surface	Steel

Description

Sleeve brushes
Sleeve brushes from LESSMANN are particularly stable tube brushes with their filling cut in conical shape. They are used primarily in container construction to machine-clean sleeves (with internal threads), for example after galvanising.

Brushes with double spiral
These brushes are used mainly in relatively large diameters to work on hard materials. A double spiral is more stable and more resistant to untwisting, meaning the brush can be exposed to higher forces.